



# TFH 610 Handheld Hygro Thermometers

Digital handheld hygro thermometer pen for rapid humidity and temperature measurements.



- Robust and impact resistant
- Factory calibration certificate
- Battery charge indicator
- High accuracy
- Switchable between °C/°F
- Automatic shutoff

## Description

The TFH 610, handheld hygro thermometer, is a robust and impact resistant field meter that will allow you to measure relative humidity and temperature simultaneously. The unit is highly accurate and comes with a factory calibration certificate. The instrument's large LCD shows both humidity and temperature readings at the same time. You can choose to have it display either °C or °F. In addition to having a battery charge indicator, the hygro thermometers have an automatic shutoff feature to preserve battery power.

### Alarm function

The TFH 610, handheld digital hygro thermometer is able to send a visible alarm when the humidity value is outside a desired range specified by you. In this case an alarm bell symbol blinks on the hygro thermometer's screen. The symbol continues to blink until you acknowledge the instrument's alarm.

### Applications

The TFH 610, handheld digital hygro thermometer has many applications including field measurements, manufacturing, computer rooms, laboratory, storage, and environmental control.

## Specifications

### Humidity:

*Range:* 0 to 100% rH

*Resolution:* 0.1%

*Accuracy:*  $\pm 2.5\%$  rH (from 10 to 90%)

### Temperature:

*Range:* 32 to 122°F (0 to 50°C)

*Resolution:* 0.1°F or °C

*Accuracy:*  $\pm 0.9^\circ\text{F}$  or  $\pm 0.5^\circ\text{C}$

*Sensor Type:* Capacitive (Humidity), Thermistor (Temperature)

*Operating Temperature:* 32 to 122°F (0 to 50°C)

*Storage Temperature:* -13 to 140°F (-25 to 60°C)

*Number of Measuring Channels:* 2

*Measuring Rate:* 1-15 sec.

*Power:* Lithium button cells, 3.0 V, 1000 mAh

*Battery Life:* up to 5 years

*Housing Material:* ABS

*Dimensions:* 4.5x 2.1 x 0.9 inch (115 x 54 x 22mm)

*Weight:* 2.9oz (90g)

*IP rating:* IP 40

*Certifications:* CE

## Options and Accessories

**TFH 610** - Handheld Hygro Thermometer

**AH 600** - Calibration Kit

Includes 11.1% rH, 52.7% rH, 75.4% rH calibration standards, complete with case.

Contact  
Global Water  
for all your  
instrumentation  
needs:

Water Level

Water Flow

Water Samplers

Water Quality

Weather

Remote Monitoring

Control



Global Water  
a xylem brand

In the U.S. call toll free  
at 1-800-876-1172  
International: 1-979-690-5560  
Fax: 1-979-690-0440  
Email: [globalw@globalw.com](mailto:globalw@globalw.com)

Visit our online catalog at:  
[www.globalw.com](http://www.globalw.com)  
Our Address:  
11390 Amalgam Way  
Gold River, CA 95670