

# DO600 Dissolved Oxygen Meter



- Measures % saturation and concentration
- Adjustable altitude compensation
- Adjustable salinity compensation
- Analog bar graph
- Saves up to 25 readings
- Self calibration on power up

## Description

The DO600 Dissolved Oxygen Meter can display the oxygen level as % saturation from 0-200% or concentration from 0-20.00 ppm (mg/L). The dissolved oxygen meter also has the ability to adjust for altitude (0-20,000 ft in 1,000 ft increments) and for salinity from 0 to 50 ppt. The dissolved oxygen meter displays the oxygen level on a large LCD screen that supports an analog bar graph to indicate trends, a data hold feature, and a low battery indicator.

The DO600 Dissolved Oxygen Meter was designed to be easy to use in harsh environments. The dissolved oxygen meter is waterproof to the IP67 standard, self calibrates on power up, and supports an automatic power shut off feature. The dissolved oxygen meter includes the DO electrode, protective sensor cap, spare membrane cap, electrolyte, four 1.5V SR44W batteries, and a 48" (1.2m) neckstrap.

## Specifications

*DO:* 0 to 200.0% / 0 to 20.00ppm (mg/L)  
*Temperature Range:* 32° to 122°F (0° to 50°C)  
*Max. Resolution:* 0.1%, 0.01ppm (mg/L), 0.1°F/ °C  
*Accuracy:* ±2.0%FS, 0.4ppm (mg/L), ±1.8°F/1°C  
*Power:* four SR44W button batteries  
*Size:* 1.4x6.9x1.6" (36x176x41mm)  
*Weight:* 3.8oz (110g)

## Options and Accessories

### DO600 Dissolved Oxygen Meter

Includes DO electrode, protective sensor cap, spare membrane cap, electrolyte, four 1.5V SR44W batteries, and a 48" (1.2m) neckstrap.

### DO605

Spare dissolved oxygen meter electrode

### DO603

Membrane Kit for Dissolved Oxygen Meter Electrode

### CA895

Carrying Case, Small with Belt Loop

Contact  
Global Water  
for all your  
instrumentation  
needs:

Water Level

Water Flow

Water Samplers

Water Quality

Weather

Remote Monitoring

Control



Global Water  
a xylem brand

In the U.S. call toll free  
at 1-800-876-1172  
International: 1-979-690-5560  
Fax: 1-979-690-0440  
Email: [globalw@globalw.com](mailto:globalw@globalw.com)

Visit our online catalog at:  
[www.globalw.com](http://www.globalw.com)  
Our Address:  
11390 Amalgam Way  
Gold River, CA 95670