F-450N & F-451N Inline Flowmeters

Variable Area Inline Flowmeters



Features

- Rugged polysulfone body
- Union connectors for easy cleaning

Specifications

•			
Accuracy	±5% full scale		
Materials	Body: Polysulfone		
	Adapter: Polysulfone		
	Float: 316 SS or PTFE		
	O-rings: Viton®		
	Half union: Anodized aluminum		
Maximum Pressure	150 psi (10.3 bar) @ 70°F (21°C)		
Maximum Pressure Drop	2 psi		
Maximum Fluid Temperature	212°F (100°C)		
Dimensions	F-450N: 10" height x 1-7/8" dia. (25.4 height x 4.8 cm dia.)		
	F-451N: 14" height x 3-3/16" dia. (35.6 height x 8.1 cm dia.)		
Weight (Approx.)	F-450N: ½ lb (0.23 kg)		
	F-451N: 3 lb (1.4 kg)		

Description

The F-450N and F-451N Variable Area Inline Flowmeters cover a wide range of flows and can handle many kinds of liquids. Designed to last, these flowmeters feature a polysulfone body, PVC connectors, and a stainless steel float and guide rod. The handy union connectors facilitate easy removal for periodic cleaning. Choose from a variety of flow ranges and the three connection sizes listed in the ordering section below. Other connection sizes, rate valves, and panel mount versions are available by special order- please contact Global Water regarding this option.

Order No.	Flow Range (gpm)	Flow Range (lpm)
F-45375LHN-8	0.1 to 1	0.4 to 4.4
F-45376LHN-8	0.2 to 2.0	1.0 to 7.5
F-45500LHN-8	0.5 to 5.0	2.0 to 20.0
F-45500LHN-12	0.5 to 5.0	2.0 to 20.0

Ordering & Options

Order No.	Flow Range (gpm)	Flow Range (lpm)	Connection
F-45375LHN-8	0.1 to 1	0.4 to 4.4	1/2" NPT (M)
F-45376LHN-8	0.2 to 2.0	1.0 to 7.5	1/2" NPT (M)
F-45500LHN-8	0.5 to 5.0	2.0 to 20.0	1/2" NPT (M)
F-45500LHN-12	0.5 to 5.0	2.0 to 20.0	3/4" NPT (M)
F-45750LHN-12	1.0 to 10.0	4.0 to 40.0	3/4" NPT (M)
F-451002LHN	2.0 to 20.0	7.5 to 75.0	1 " NPT (F)
F-451003LHN	3.0 to 30.0	12.0 to 115.0	1 " NPT (F)
F-451004LHN	4.0 to 40.0	15.0 to 155.0	1 " NPT (F)



In the U.S. call toll free at 1-800-876-1172 International: 1-979-690-5560 Fax: 1-979-690-0440 Email: globalw@globalw.com

Visit our online catalog at: www.globalw.com Our Address: 11390 Amalgam Way Gold River, CA 95670